

# เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



APC Smart-UPS C, Line Interactive, 1000VA, Tower, 230V, 8x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD

SMC1000IC

## Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock

## Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	600 W
Rated power in VA	1000 VA
Input Connection Type	IEC 320 C14
Output connection type	8 IEC 60320 C13
Battery type	Lead-acid battery
Provided equipment	Power cord USB cable

## Complementary

Software package	SmartConnect software for remote power monitoring feature availability varies by terms of use
------------------	-----------------------------------------------------------------------------------------------

## General

Number of power module filled slots	0
Number of power module free slots	0
Product web sub-family	Cloud-enabled monitoring
Redundant	No

## Physical

Colour	Black
Height	21.9 cm

<b>Width</b>	17.1 cm
<b>Depth</b>	43.9 cm
<b>Net weight</b>	17.27 kg
<b>Mounting location</b>	Front
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Not rack-mountable
<b>Two post mountable</b>	0
<b>USB compatible</b>	Yes

## Input

<b>Input voltage limits</b>	170...300 V adjustable 180...287 V
<b>Network frequency</b>	50/60 Hz +/- 3 Hz auto-sensing

## Output

<b>Harmonic distortion</b>	Less than 5 %
<b>Maximum configurable power in VA</b>	1000 VA
<b>Maximum configurable power in W</b>	600 W
<b>Transfer time</b>	6 ms typical : 10 ms maximum
<b>UPS type</b>	Line interactive
<b>Wave type</b>	Sine wave
<b>Output frequency</b>	50/60 Hz +/- 3 Hz sync to mains

## Conformance


<b>Product certifications</b>	CE GOST VDE
<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

<b>Acoustic level</b>	41 dBA
<b>Heat dissipation</b>	100 Btu/h
<b>Operating altitude</b>	0...10000 ft
<b>Ambient air temperature for operation</b>	0...40 °C
<b>Ambient air temperature for storage</b>	-15...45 °C
<b>Storage altitude</b>	0.00...15240.00 m
<b>Relative humidity</b>	0...95 %
<b>Storage Relative Humidity</b>	0...95 %

## Batteries & Runtime

<b>Extended runtime</b>	0
<b>Number of battery filled slots</b>	0
<b>Number of battery free slots</b>	0

Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC142</a> 
Battery power in VAH	216 VAh runtime
Battery charger power	72 W rated

## Communications & Management

Control panel	Multifunction LCD status and control console
Free slots	0
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

Surge energy rate	455 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	37.6 cm
Package 1 Width	59.5 cm
Package 1 Length	32.8 cm
Package 1 Weight	19.55 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

ผลิตภัณฑ์ทดแทนที่แนะนำ